



The World's First RTK Receiver for Every Mobile Device

The Arrow 200 is the world's first GNSS receiver able to provide 1cm real-time accuracy on your Android, iOS and Windows mobile device. Yes, you can enjoy 1cm accuracy on your iPhone or Samsung Galaxy running Esri Collector, ArcGIS for iOS or whatever app software you prefer, even AutoCAD 360!

Designed for use with a broad range of mobile devices, from smartphones to tablets and notebook computers, the Arrow 200 incorporates rock-solid, wireless Bluetooth® technology that works smoothly with Android, iOS and Windows® devices, making it obsolete-proof and portable across platforms.

Use the Mobile GIS Software of your choice

Seems like a new Mobile GIS software is being offered each week? With Arrow Lite you will not be tied to legacy GNSS receiver hardware or GIS software, the Arrow 200 will grow with you.

The Arrow 200 feeds 1cm RTK accuracy to every app on your Android or iOS device, even Google or Apple maps! Esri Collector/ArcPad/ArcMobile, Fulcrum, AmigoCloud, TerraFlex, MapItFast, GeoJot, iCMTGIS, the Arrow 200 works seamlessly with all of them and many more mapping apps.

All Satellites, All Signals

The Arrow 200 incorporates premium features that place it among the highest performing receivers in the world. It takes advantage of all existing satellite constellations (GPS, GLONASS, BeiDou, SBAS) as well as emerging and planned constellations (Galileo and QZSS) to deliver top-notch, 1cm RTK performance anywhere in the world when connected to an RTK Network or 10-15cm accuracy using OmniSTAR HP or G2.

ARROW 200™

ARROW Series
for 1-3cm Accuracy with RTK

Key Features:

- Supports existing and future GNSS (GPS, GLONASS, Galileo, BeiDou, QZSS)
- 100% Android, iOS, Windows compatible.
- 1cm RTK real-time accuracy.
- Supports Esri® and other Mobile GIS software
- Supports OmniSTAR® HP and G2 service



The Ultimate in World-wide High-Precision GNSS Technology

The Arrow 200 provides the ultimate in flexibility. Using your smartphone, tablet or notebook computer, it can deliver 1cm real-time accuracy when connected to an RTK Network or RTK base. No RTK base? Then use one of OmniSTAR's services to get 10cm real-time accuracy anywhere in the world.

Just want to post-process? You can collect data anywhere in the world using Eos' free data collection program and post-process the data using free online processing services like OPUS or AUSPOS to achieve centimeter accuracy anywhere in the world.



For more details,
www.eos-gnss.com

Specifications

GPS Sensor

Receiver type:	GNSS multi-frequency RTK with carrier phase
Signals Received:	GPS, GLONASS, BeiDou, Galileo and QZSS
Channels:	372 total, parallel tracking
Number of tracked satellites:	12 GPS 12 GLONASS 22 BeiDou (Galileo & QZSS, TBA)
SBAS Support:	3 Satellite parallel tracking WAAS/EGNOS/MSAS/GAGAN (with SBAS ranging)
Update rate:	1Hz Default, optional 10Hz and 20Hz
RTK Accuracy:	1cm ¹ + 1ppm Horizontal
SBAS Accuracy:	<30cm HRMS ¹
Autonomous Accuracy:	1.2 meters HRMS ¹
Cold start:	< 60 sec typical (no almanac or time)
Reacquisition:	< 1 sec
Max speed:	1,850 kph / 999 knots / 1,150 mph
Max altitude:	18,288 meters / 60,000 ft

Communication

Port:	Bluetooth, USB 2.0
Bluetooth Transmission:	Class 1, 300m typical range ² , up to 1km
Frequency:	2.400 - 2.485 GHz
Fully Bluetooth pre-qualified:	Bluetooth 2.1 + EDR
Supported Bluetooth Profiles:	SPP and iAP
Data I/O formats:	NMEA 0183, RTCM 104, Binary
Output datum:	Autonomous: WGS-84 (G1674) Epoch 2005.0 SBAS: ITRF08 (current year epoch) RTK: Same as RTK base
Raw Measurement Data:	Binary and RINEX
Correction I/O Protocol:	RTCM 2.x, 3.x, CMR, CMR+, proprietary binary
GPS Status LEDs:	Power, GNSS, DGNSS, DIFF, Bluetooth
Battery Status LED:	5 LED Indicator

Power

Battery type:	Field replaceable, rechargeable Lithium-Ion pack. Rechargeable inside unit or separately
Battery life:	8+ hours ³ (without OmniSTAR activated)
Charging time:	4 hours (vehicule charger available)

Environmental

Operating Temperature:	-40°C to +85°C (-40°F to +185°F) ³
Storage Temperature:	-40°C to +85°C (-40°F to +185°F)
Humidity:	95% non-condensing
Compliance:	FCC, CE, RoHS and Lead-free



Eos Positioning Systems Inc.
Terrebonne (Quebec), Canada
Tel: (514) 949-5180
www.eos-gnss.com | info@eos-gnss.com

Mechanical

Enclosure Material:	Re-enforced Nylon & ABS
Enclosure Rating:	Waterproof, IP-67
Immersion:	30cm, 30 minutes
Dimensions:	12.5 x 8.4 x 4.2 cm (4.92 x 3.3 x 1.65 in.)
Weight:	372g (0.82 lbs)
Data Connectors:	Mini USB Type B Receptacle
Antenna Connector:	SMA Female

Antenna

GPS Freq Range:	1525 - 1607 MHz, 1217 - 1260 MHz
Impedance:	50 OHMs
Gain (no cable):	29dB ±2dB
Noise Figure:	2.5dB Max
Voltage:	+4.5 to +15 VDC
Connector:	SMA female
Dimensions:	26.6 mm H x 66.3 mm D (0.86 in H x 2.6 in D)
Weight:	165 g (0.363 lb)
Temperature:	-55°C to +70°C (-67°F to + 158°F)
Humidity:	Waterproof

Standard Accessories

Li-Ion Battery Pack (Field replaceable)	Pole Bracket and Clamp
12VDC Power Supply	Hard Shell Case
USB Cable	Antenna Cable (1.5 meter)
Belt/Shoulder Carrying Case	Soft Hat for antenna
L1/L2, L-Band GNSS Antenna	Antenna Mounting Plate

Field Activated Options

10Hz, 20Hz Output Rates
GLONASS, BeiDou (Galileo, QZSS future options)
RTK Base/Rover

NOTES :

1. Depends on multipath environment, number of satellites in view, satellite geometry, baseline length (for local services) and ionospheric activities. Stated accuracies for baseline lengths of up to 50 km
2. Transmission in free space
3. Lithium-Ion battery performance degrades below -20°C (-4°F)

© Copyright July 2014, Eos Positioning Systems Inc. All rights reserved. Specifications subject to change without notice. Arrow Lite™, Arrow Series™ are trademarks of Eos Positioning Systems Inc., Canada. The Bluetooth™ trademarks are owned by Bluetooth SIG, Inc, U.S.A. All other trademarks are the property of their respective owners.

Made in Canada 🇨🇦

Authorized Distributor